



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDR-43 SERIES

PART NO.	INDUCTANCE (μ H)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDR-43-1R0 □	1.0	7.96M	0.033	3.80
SDR-43-1R4 □	1.4	7.96M	0.038	3.30
SDR-43-1R8 □	1.8	7.96M	0.042	2.91
SDR-43-2R2 □	2.2	7.96M	0.047	2.60
SDR-43-2R7 □	2.7	7.96M	0.052	2.43
SDR-43-3R3 □	3.3	7.96M	0.058	2.15
SDR-43-3R9 □	3.9	7.96M	0.076	1.98
SDR-43-4R7 □	4.7	7.96M	0.094	1.70
SDR-43-5R6 □	5.6	7.96M	0.101	1.60
SDR-43-6R8 □	6.8	7.96M	0.117	1.41
SDR-43-8R2 □	8.2	7.96M	0.132	1.26
SDR-43-100 □	10	2.52M	0.182	1.15
SDR-43-120 □	12	2.52M	0.210	1.05
SDR-43-150 □	15	2.52M	0.235	0.92
SDR-43-180 □	18	2.52M	0.338	0.84
SDR-43-220 □	22	2.52M	0.378	0.76
SDR-43-270 □	27	2.52M	0.522	0.71
SDR-43-330 □	33	2.52M	0.540	0.64
SDR-43-390 □	39	2.52M	0.587	0.59
SDR-43-470 □	47	2.52M	0.844	0.54
SDR-43-560 □	56	2.52M	0.937	0.50
SDR-43-680 □	68	2.52M	1.100	0.46
SDR-43-820 □	82	2.52M	1.117	0.46
SDR-43-101 □	100	1.00K	1.200	0.22
SDR-43-121 □	120	1.00K	1.600	0.20
SDR-43-151 □	150	1.00K	2.000	0.20
SDR-43-181 □	180	1.00K	3.000	0.20
SDR-43-221 □	220	1.00K	3.000	0.20
SDR-43-271 □	270	1.00K	4.000	0.16
SDR-43-331 □	330	1.00K	4.000	0.14
SDR-43-391 □	390	1.00K	5.000	0.12
SDR-43-471 □	470	1.00K	6.000	0.12
SDR-43-561 □	560	1.00K	7.000	0.10
SDR-43-322 □	3200	1.00K	32.00	0.06
SDR-43-682 □	6800	1.00K	57.00	0.05
SDR-43-902 □	9000	1.00K	93.00	0.045
SDR-43-223 □	22000	1.00K	376.0	0.03

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME