

SMT POWER INDUCTORS (SI321618/322520/453226)

Various high power inductors are superior to be high saturation for surface mounting.

Applications: Power supply for VTR, OA equipment, LCD television set, notebook PC, portable communication equipment DC/DC converters etc.

PRODUCT IDENTIFICATION

SD- SI-□□-□□□-□

1. 2. 3. 4. 5.

(1) MODEL


(2) SERIES

(3) SIZE


(4) INDUCTANCE

(5) TOLERANCE (J:±5%, K:±10%, E:±15%, M:±20%, T:±30%)


CONFIGURATIONS & DIMENSIONS



SIDE VIEW



C



BOTTOM VIEW

TYPE	A	B	C	D	E	F	G
SI-321618	2.3±0.2	2.1(MAX)	3.2±0.3	1.6±0.2	1.0(MIN)	1.0(MIN)	1.6±0.2
SI-322520	2.5±0.2	2.5(MAX)	3.2±0.3	2.5±0.2	1.0(MIN)	1.0(MIN)	2.5±0.2
SI-453226	3.6±0.2	2.9(MAX)	4.5±0.3	3.2±0.2	1.0(MIN)	1.0(MIN)	3.2±0.2

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME