



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDS-075D/125D SERIES

PART NO.	INDUCTANCE (uH)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDS-075D-100 □	10	1.00K	0.049	1.84
SDS-075D-120 □	12	1.00K	0.058	1.71
SDS-075D-150 □	15	1.00K	0.081	1.47
SDS-075D-180 □	18	1.00K	0.091	1.31
SDS-075D-220 □	22	1.00K	0.110	1.23
SDS-075D-270 □	27	1.00K	0.150	1.12
SDS-075D-330 □	33	1.00K	0.170	0.96
SDS-075D-390 □	39	1.00K	0.230	0.91
SDS-075D-470 □	47	1.00K	0.260	0.88
SDS-075D-560 □	56	1.00K	0.350	0.75
SDS-075D-680 □	68	1.00K	0.380	0.69
SDS-075D-820 □	82	1.00K	0.430	0.61
SDS-075D-101 □	100	1.00K	0.610	0.60
SDS-125D-3R3 □	3.3	100K	0.015	6.50
SDS-125D-4R7 □	4.7	100K	0.018	5.70
SDS-125D-6R8 □	6.8	100K	0.023	4.90
SDS-125D-100 □	10	1.00K	0.028	4.50
SDS-125D-120 □	12	1.00K	0.038	4.00
SDS-125D-150 □	15	1.00K	0.052	3.20
SDS-125D-180 □	18	1.00K	0.060	3.10
SDS-125D-220 □	22	1.00K	0.070	2.90
SDS-125D-270 □	27	1.00K	0.080	2.80
SDS-125D-330 □	33	1.00K	0.097	2.70
SDS-125D-390 □	39	1.00K	0.132	2.10
SDS-125D-470 □	47	1.00K	0.150	1.90
SDS-125D-560 □	56	1.00K	0.190	1.80
SDS-125D-680 □	68	1.00K	0.220	1.50
SDS-125D-820 □	82	1.00K	0.260	1.30
SDS-125D-101 □	100	1.00K	0.308	1.20
SDS-125D-121 □	120	1.00K	0.380	1.10
SDS-125D-151 □	150	1.00K	0.520	0.95
SDS-125D-181 □	180	1.00K	0.600	0.85
SDS-125D-221 □	220	1.00K	0.700	0.80
SDS-125D-271 □	270	1.00K	0.860	0.60
SDS-125D-331 □	330	1.00K	0.980	0.50

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME