



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDS-128D SERIES

PART NO.	INDUCTANCE (μ H)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDS-128D-1R2 □	1.2	100K	0.0070	9.80
SDS-128D-2R7 □	2.7	100K	0.0115	8.00
SDS-128D-3R9 □	3.9	100K	0.0135	7.50
SDS-128D-4R7 □	4.7	100K	0.0158	6.80
SDS-128D-5R6 □	5.6	100K	0.0176	6.60
SDS-128D-7R5 □	7.5	100K	0.0200	5.90
SDS-128D-100 □	10	1.00K	0.0216	5.40
SDS-128D-120 □	12	1.00K	0.0243	4.90
SDS-128D-150 □	15	1.00K	0.0270	4.50
SDS-128D-180 □	18	1.00K	0.0392	3.90
SDS-128D-220 □	22	1.00K	0.0432	3.60
SDS-128D-270 □	27	1.00K	0.0459	3.40
SDS-128D-330 □	33	1.00K	0.0648	3.00
SDS-128D-390 □	39	1.00K	0.0729	2.75
SDS-128D-470 □	47	1.00K	0.1000	2.50
SDS-128D-560 □	56	1.00K	0.1100	2.35
SDS-128D-680 □	68	1.00K	0.1400	2.10
SDS-128D-820 □	82	1.00K	0.1600	1.95
SDS-128D-101 □	100	1.00K	0.2200	1.70
SDS-128D-121 □	120	1.00K	0.2500	1.60
SDS-128D-151 □	150	1.00K	0.2800	1.42
SDS-128D-181 □	180	1.00K	0.3500	1.30
SDS-128D-221 □	220	1.00K	0.3900	1.16
SDS-128D-271 □	270	1.00K	0.5600	1.06
SDS-128D-331 □	330	1.00K	0.6400	0.95
SDS-128D-391 □	390	1.00K	0.7000	0.88
SDS-128D-471 □	470	1.00K	0.9800	0.79
SDS-128D-561 □	560	1.00K	1.0700	0.73
SDS-128D-681 □	680	1.00K	1.4600	0.67
SDS-128D-821 □	820	1.00K	1.6400	0.60
SDS-128D-102 □	1000	1.00K	1.8200	0.55

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME