



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDOS-3316 SERIES

PART NO.	INDUCTANCE (μ H)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDOS-3316-1R0 <input type="checkbox"/>	1.0	100K	0.021	5.60
SDOS-3316-1R5 <input type="checkbox"/>	1.5	100K	0.022	5.20
SDOS-3316-2R2 <input type="checkbox"/>	2.2	100K	0.032	5.00
SDOS-3316-3R3 <input type="checkbox"/>	3.3	100K	0.039	3.90
SDOS-3316-4R7 <input type="checkbox"/>	4.7	100K	0.054	3.20
SDOS-3316-6R8 <input type="checkbox"/>	6.8	100K	0.075	2.80
SDOS-3316-100 <input type="checkbox"/>	10.0	100K	0.101	2.40
SDOS-3316-150 <input type="checkbox"/>	15.0	100K	0.150	2.00
SDOS-3316-220 <input type="checkbox"/>	22.0	100K	0.207	1.60
SDOS-3316-330 <input type="checkbox"/>	33.0	100K	0.334	1.40
SDOS-3316-470 <input type="checkbox"/>	47.0	100K	0.472	1.00

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME