



SMT POWER INDUCTORS (SDR32/43/54/73/75/104/105)

Various high power inductors are superior to be high saturation for surface mounting.

Applications: Power supply for VTR, OA equipment, LCD television set, notebook PC, portable communication equipment DC/DC converters etc.

PRODUCT IDENTIFICATION

SD - SDR - □□ - □□□ - □

1. 2. 3. 4. 5.

(1) MODEL


(2) SERIES

(3) SIZE



(4) INDUCTANCE

(5) TOLERANCE (J:±5%, K:±10%, E:±15%, M:±20%, T:±30%)

CONFIGURATIONS & DIMENSIONS



TOP VIEW



BOTTOM VIEW

TYPE	A	B	C	D
SDR-32	MAX:3.5	2.1±0.3	3.5±0.3	1.0±0.3
SDR-43	MAX:4.6	3.2±0.3	4.5±0.3	1.2±0.3
SDR-52	MAX:5.5	2.0±0.3	5.8±0.3	2.2±0.3
SDR-54	MAX:5.5	4.5±0.3	5.8±0.3	2.2±0.3
SDR-73	MAX:7.3	3.5±0.3	7.8±0.3	2.5±0.3
SDR-75	MAX:7.3	5.2±0.3	7.8±0.3	2.5±0.3
SDR-104	MAX:9.3	4.4±0.3	10.0±0.3	3.0±0.3
SDR-105	MAX:9.3	5.4±0.3	10.0±0.3	3.0±0.3

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME